

SUPERIORITY

- · Well-developed micropore area
- · Large surface area
- · High hardness

APPLICATION

- · Purification of water drainage
- · Purification of water supply
- · Air purification
- · Furniture removal of formaldehyde

CERTIFICATES

- · ISO 9001
- · ISO 14001
- · ISO 45000

PACKAGING

· Inner packing: PE bag Outer packing: PP woven

bag/kraft bag

· 25kg/bag (carton)
(Packaging can be customized)

MG SERIES

MG series is divided into raw coal crushed carbon and pressure column crushed carbon. Using high-quality raw coal as raw material, it is refined through high-temperature carbonization, activation, screening and other processes. With developed surface area and microporous structure, it is suitable for deep purification of water supply and drainage and air purification treatment.

General Properties					
lodine Value	mg/g	[1]	500-1100		
Particle Size	mesh	[1]	4X8, 8x30, 12x40 , 20x40, 20x50		
Hardness	%	[1]	85-98		
Ash Content	%	[1]	10-20		
Moisture Content	%	[1]	≤ 5		
рН		[1]	6–11		

Typical Characteristics				
Bulk Density	g/mI	[1]	0. 42-0. 55	
Methylene Blue Adsorption	mg/g	[1]	100-240	

Test standard:

[1] GB/T 7702

