

PRODUCT NAME : MFCARB WT E1240  
 APPLICATION AREA : For Water treatment  
 ACTIVATION AGENT : STEAM/AIR  
 MESH SIZE : 12X40 USS MESH

PARAMETER	UNIT	RESULTS TEST	METHOD
Moisture	%	3 %Max	ASTM D2867
Bulk density	Kg/m3	480 min	ASTM D 2854
Ash Content	%	4 Max	ASTM D 2866
pH		9-11	ASTM D 3838
CTC	%	60	ASTM D 3467
Iodine Number	mg/g	1000-1200	ASTM D 4607
Surface Area	m2/g	1150min	BET-m2
Ball Pan Hardness	No	98 min	ASTM D3802

PARTICLE SIZE DISTRIBUTION			
+12 USS MESH	%	5 max	ASTM D 2862
-40 USS MESH	%	5 max	ASTM D 2862

**PACKING** The material is packaged in 500kgs net in poly woven bags or 25kgs net in PP bags with inner lining will be shrink wrapped and palletized in to fumigated Pallets as per ISPM 15 standard.

**STORAGE:** Store the material in a cool dry area, away from sunlight.

**SHELF LIFE:** More than 5 Years when keeping in proper packed condition

**LABELING:** The label displays the product name, lot number, net weight, gross weight, manufacturer name & address and other information or marks as required by the customer

