


HF/HF3-Series High Flow Pleated

HF-Series High Flow Polypropylene and Micro-glass Filter Cartridges address your need for absolute rated filter cartridges in high flowrate applications. HF-Series cartridges are designed for use as a direct replacement to the Pall[®] Ultipleat[®] High Flow and 3M 740[™] series elements. Filtration efficiencies exceed 99%.

Flow Rate vs Pressure Drop





Construction Materials

Filtration Media		
	or Microglass	
Support Media	Polypropylene	
End Caps	Polypropylene	
Center Core	Polypropylene	
Outer Support Cage	Polypropylene	
O-Rings/Gaskets	Buna, EPDM,	
	Silicone, Viton®	

Operating Conditions

Change Out ΔP (recommended)........35 PSID
Polypropylene Temperature (max)....160°F (71°C)
Microglass Temperature (max)........................60 PSID

(4.1 bar) at 68°F (20°C)

Food Safety Compliance

Materials of construction comply with FDA regulations for food and beverage contact use as detailed in the US Code of Federal Regulations, 21CFR. Materials used to produce filter media and hardware are deemed safe for use in contact with foodstuffs in accordance with EU Directives 2002/72/EC, 1935/2004, and/or 10/2011.

Dimensions

Length:

HF - 20, 40, 60 inches

HF3 - 39 inches

Outside Diameter:

6.25 inches

Ordering Information

Туре	Material	Rating (μ)	Α	Length	O-Rings
HF	PP = Polypropylene	0.45	A= Absolute	20" = HF (50.8 cm)	B = Buna
Retrofits Pall® HF	FG = Microglass	1.0		39" = HF3 (99.1 cm)	E = EPDM
		5.0		40" = HF (101.6 cm)	S = Silicone
HF3		10.0		60" = HF (152.4 cm)	V = Viton®
Retrofits 3M™ - 740		20.0			
		50.0			
		100.0			

Pall® is a registered trademark of Pall® Corporation

DS_HF_190918

